according to Regulation (EC) No 1907/2006

TechSil Gum (Part A)

Revision date: 11.06.2019

Page 1 of 11

Product Code(s): 320C, G35C, G65C 1.2. Relevant identified uses of the substance or mixture and uses advised against High cons 1.3. Details of the supplier of the safety data sheet Company name: Technovent Ltd Street: Unit 5 York Park Bridgend CF31 3TB Place: UK Telephone: +44 1656 768566 9-mail: info@technovent.com Internet: www.technovent.com Emergency number: +44 1656768566 This number is only obtainable during office hours (Monday - Thursday 9.00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) 1.4. Emergency telephone number	Product Name:		
320C, G35C, Gé5C 1.2. Relevant identified uses of the substance or mixture and uses advised against High cons 1.3. Details of the supplier of the safety data sheet Company name: Technovent Ltd Street: Bridgend CF31 3TB Place: UK Telephone: +44 1656 768566 e-mail: info@technovent.com Emergency number: +44 1656768566 This number is only obtainable during office hours (Monday - Thursday 9.00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) 1.4. Emergency telephone number +4401656 768566 This number is only obtainable during office hours (Monday - Thursday 8.00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) Generic Description: Silicone Physical Form: Rubber-Gum Color: Tan Odor: Not available NEPA Profile: Health 0 Flammability 1 Instability/Reactivity 0	TechSil Gum (Part A)		
High cons 1.3. Details of the supplier of the safety data sheet. Company name: Technovent Ltd Street: Unit 5 York Park Bridgend CF31 3TB Place: UK Telephone: +44 1656 768566 mail: info@technovent.com Internet: www.technovent.com Emergency number: +44 1656768566 This number is only obtainable during office hours Monday - Thursday 9.00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) 1.4.Emergency telephone number +4401656 768566 This number is only obtainable during office hours Monday - Thursday 9.00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) Company and the secret protein: Silicone Physical Form: Rubber-Gum Color: Tan Odor: Not available NFPA Profile: Healt 0 Flammability 1 Instability/Reactivity 0	Product Code(s): G20C, G35C, G65C		
1.3. Details of the supplier of the safety data sheet Company name: Technovent Ltd Street: Unit 5 York Park Bridgend CF31 3TB Place: UK Telephone: +44 1656 768566 e-mail: info@technovent.com terret: www.technovent.com Emergency number: +44 1656768566 This number is only obtainable during office hours (Monday - Thursday 9.00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) 1.4. Emergency telephone number +4401656 768566 This number is only obtainable during office hours (Monday - Thursday 8.00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) Generic Description: Silicone Physical Form: Rubber-Gum Color: Tan Odd: Not available NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0	1.2. Relevant identifie	d uses of the substance or mixture and uses advised against	
Company name: Technovent Ltd Street: Unit 5 York Park Bridgend CF31 3TB Place: UK Telephone: +44 1656 768566 a-mail: info@technovent.com internet: www.technovent.com Emergency number: +44 1656768566 This number is only obtainable during office hours (Monday - Thursday 9.00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) 1.4. Emergency telephone number +4401656 768566 This number is only obtainable during office hours (Monday - Thursday 8.00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) Constant Generic Description: Silicone Physical Form: Rubber-Gum Color: Tan Odor: Not available NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0	High cons		
Street: Unit 5 York Park Bridgend CF31 3TB Place: Place: UK Felephone: +44 1656 768566 a-mail: info@technovent.com termergency number: +44 1656768566 This number is only obtainable during office hours (Monday - Thursday 9.00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) 14.4 Emergency telephone number +4401656 768566 This number is only obtainable during office hours (Monday - Thursday 8.00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) Clear is only obtainable during office hours (Monday - Thursday 8.00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) Generic Description: Silicone Physical Form: Rubber-Gum Color: Tan Odor: Not available NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0	1.3. Details of the sup		
Bridgend CF31 3TB Place: UK Telephone: +44 1656 768566 e-mail: info@technovent.com mternet: www.technovent.com Emergency number: +44 1656768566 This number is only obtainable during office hours (Monday - Thursday 9.00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) 1.4. Emergency telephone number +4401656 768566 This number is only obtainable during office hours (Monday - Thursday 8.00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) Generic Description: Silicone Physical Form: Rubber-Gum Color: Tan Odor: Not available NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0	Company name:		
Place: UK Telephone: +44 1656 768566 mail: info@technovent.com internet: www.technovent.com Emergency number: +44 1656768566 This number is only obtainable during office hours (Monday - Thursday 9.00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) 1.4. Emergency telephone number +4401656 768566 This number is only obtainable during office hours (Monday - Thursday 8.00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) Generic Description: Silicone Physical Form: Rubber-Gum Color: Tan Odor: Not available NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0	Street:		
Telephone: +44 1656 768566 e-mail: info@technovent.com nternet: www.technovent.com Emergency number: +44 1656768566 This number is only obtainable during office hours Monday - Thursday 9.00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) 1.4. Emergency telephone number +4401656 768566 This number is only obtainable during office hours Monday - Thursday 8.00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) Generic Description: Silicone Physical Form: Rubber-Gum Color: Tan Odor: Not available NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0			
e-mail: info@technovent.com Internet: www.technovent.com Emergency number: +44 1656768566 This number is only obtainable during office hours (Monday - Thursday 9.00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) 1.4. Emergency telephone number +4401656 768566 This number is only obtainable during office hours (Monday - Thursday 8.00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) Generic Description: Silicone Physical Form: Rubber-Gum Color: Tan Odor: Not available NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0			
Internet: www.technovent.com Emergency number: +44 1656768566 This number is only obtainable during office hours (Monday - Thursday 9.00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) 1.4. Emergency telephone number +4401656 768566 This number is only obtainable during office hours (Monday - Thursday 8.00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) Generic Description: Silicone Physical Form: Rubber-Gum Color: Tan Odor: Not available NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0			
Emergency number: +44 1656768566 This number is only obtainable during office hours Monday - Thursday 9.00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) 1.4. Emergency telephone number +4401656 768566 This number is only obtainable during office hours Monday - Thursday 8.00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) Generic Description: Silicone Physical Form: Rubber-Gum Color: Tan Odor: Not available NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0			
This number is only obtainable during office hours (Monday - Thursday 9.00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) 1.4. Emergency telephone number +4401656 768566 This number is only obtainable during office hours (Monday - Thursday 8.00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) Generic Description: Silicone Physical Form: Rubber-Gum Color: Tan Odor: Not available NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0	nternet:	www.technovent.com	
(Monday - Thursday 9.00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) 1.4. Emergency telephone number +4401656 768566 This number is only obtainable during office hours (Monday - Thursday 8.00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) Generic Description: Silicone Physical Form: Rubber-Gum Color: Tan Odor: Not available NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0	Emergency number: +44 1656768566		
(Monday - Thursday 9.00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) 1.4. Emergency telephone number +4401656 768566 This number is only obtainable during office hours (Monday - Thursday 8.00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) Generic Description: Silicone Physical Form: Rubber-Gum Color: Tan Odor: Not available NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0	mergency number:	+44 1656768566	
1.4. Emergency telephone number +4401656 768566 This number is only obtainable during office hours (Monday - Thursday 8.00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) Generic Description: Silicone Physical Form: Rubber-Gum Color: Tan Odor: Not available NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0			
+4401656 768566 This number is only obtainable during office hours (Monday - Thursday 8.00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) Generic Description: Silicone Physical Form: Rubber-Gum Color: Tan Odor: Not available NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0	This number is only obt	ainable during office hours	
+4401656 768566 This number is only obtainable during office hours (Monday - Thursday 8.00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) Generic Description: Silicone Physical Form: Rubber-Gum Color: Tan Odor: Not available NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0	This number is only obt	ainable during office hours	
Monday - Thursday 8.00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) Generic Description: Silicone Physical Form: Rubber-Gum Color: Tan Odor: Not available NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0	This number is only obt Monday - Thursday 9.0	ainable during office hours)0 am - 5.00 pm, Friday 9.00 am - 4.00 pm)	
(Monday - Thursday 8.00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) Generic Description: Silicone Physical Form: Rubber-Gum Color: Tan Odor: Not available NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0	This number is only obt (Monday - Thursday 9.0 1.4. Emergency teleph	ainable during office hours)0 am - 5.00 pm, Friday 9.00 am - 4.00 pm)	
Generic Description: Silicone Physical Form: Rubber-Gum Color: Tan Odor: Not available NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0	This number is only obt (Monday - Thursday 9.0 1.4. Emergency teleph	ainable during office hours)0 am - 5.00 pm, Friday 9.00 am - 4.00 pm)	
Physical Form: Rubber-Gum Color: Tan Odor: Not available NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0	This number is only obt Monday - Thursday 9.0 1.4. Emergency teleph +4401656 768566 This number is only obt	ainable during office hours 00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) 100ne number ainable during office hours	
Physical Form: Rubber-Gum Color: Tan Odor: Not available NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0	This number is only obt (Monday - Thursday 9.0 1.4. Emergency teleph +4401656 768566 This number is only obt	ainable during office hours 00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) 100ne number ainable during office hours	
Physical Form: Rubber-Gum Color: Tan Odor: Not available NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0	This number is only obt (Monday - Thursday 9.0 1.4. Emergency teleph +4401656 768566 This number is only obt	ainable during office hours 00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) 100ne number ainable during office hours	
Color: Tan Odor: Not available NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0	This number is only obt (Monday - Thursday 9.0 1.4. Emergency teleph +4401656 768566 This number is only obt	ainable during office hours 00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) 100ne number ainable during office hours	
Odor: Not available NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0	This number is only obt Monday - Thursday 9.0 1.4. Emergency teleph +4401656 768566 This number is only obt Monday - Thursday 8.0	ainable during office hours 00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) none number ainable during office hours 00 am - 5.00 pm, Friday 8.00 am - 4.00 pm)	
NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0	This number is only obt Monday - Thursday 9.0 I.4. Emergency teleph +4401656 768566 This number is only obt Monday - Thursday 8.0	ainable during office hours 00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) none number ainable during office hours 00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) neric Description: Silicone Physical Form: Rubber-Gum	
	This number is only obt Monday - Thursday 9.0 I .4. Emergency teleph +4401656 768566 This number is only obt Monday - Thursday 8.0	ainable during office hours 00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) none number ainable during office hours 00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) neric Description: Silicone Physical Form: Rubber-Gum Color: Tan	
Note: NEDA National Fire Dratection Association	This number is only obt Monday - Thursday 9.0 I.4. Emergency teleph +4401656 768566 This number is only obt Monday - Thursday 8.0	ainable during office hours 00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) none number ainable during office hours 00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) neric Description: Silicone Physical Form: Rubber-Gum Color: Tan	
	This number is only obt Monday - Thursday 9.0 I .4. Emergency teleph +4401656 768566 This number is only obt Monday - Thursday 8.0	ainable during office hours 00 am - 5.00 pm, Friday 9.00 am - 4.00 pm) none number ainable during office hours 00 am - 5.00 pm, Friday 8.00 am - 4.00 pm) neric Description: Silicone Physical Form: Rubber-Gum Color: Tan Odor: Not available	

POTENTIAL HEALTH EFFECTS

Acute Effects

Skin: Inhalation: Oral:

Eye:

according to Regulation (EC) No 1907/2006

Revision date: 11.06.2019	TechSil Gum (Part A)	Page 2 of 11
No significant irritation	No significant irritation expected from a single short-term exposure.	
expected from a	No significant effects expected from a single short-term exposure.	
single exposure.	Low ingestion hazard in normal use.	
Prolonged/Repeated Ex	posure Effects	
Skin:	No known applicable information.	
Inhalation:	No known applicable information.	
Oral:	No known applicable information.	

according to Regulation (EC) No 1907/2006

TechSil Gum (Part A)

Revision date: 11.06.2019

Page 3 of 11

Signs and Symptoms of Overexposure

No known applicable information.

Medical Conditions Aggravatedby Exposure

No known applicable information.

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, com onent data and/or ex ert review of the roduct. Please refer to Section 11 for the detailed toxicolo . information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

None present. This is not a hazardous material as defined in the OSHA Hazard Communication Standard.

4. FIRST AID MEASUR	RES
Eye:	No effects expected. If irritation occurs, flush eye(s) with lukewarm gently flowing water for 5 minutes. If irritation persists, obtain medical advice.
Skin:	No health effects expected. If irritation does occur flush with lukewarm, gently flowing water for 5 minutes. If irritation persists, obtain medical advice.
Inhalation:	If symptoms are experienced remove source of contamination or move victim to fresh air. If irritation persists, obtain medical advice.
Oral:	If irritation or discomfort occur, obtain medical advice.
Notes to Physician:	Treat according to person's condition and specifics of exposure.

according to Regulation (EC) No 1907/2006

TechSil Gum (Part A)

Revision date: 11.06.2019

Page 4 of 11

5. FIRE FIGHTING MEASURES		
Flash Point:	Not applicable.	
Autoignition Temperature:	Not determined.	
Flammability Limits in Air:	Not determined.	
Extinguishing Media:	On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO2), dry chemical or water spray. Water can be used to cool fire exposed containers.	
Fire Fighting Measures:	Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Use water spray to keep fire exposed containers cool. Determine the need to evacuate or isolate the area according to your local emergency plan.	
Unusual Fire Hazards:	None.	

6. ACCIDENT AL RELEASE MEASURES

according to Regulation (EC) No 1907/2006

Revision date: 11.06.2019

TechSil Gum (Part A)

Page 5 of 11

Containment/Clean up: Observe all personal protection equipment recommendations described in Sections 5 and 8. Collect and contain for salvage or disposal. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Note: See Section 8 for Personal Protective Equipment for Spills. Call (989) 496-5900, if additional information is required.

7. HANDLING AND STORAGE

Use with adequate ventilation.

Use reasonable care and store away from oxidizing materials. This material in its finely divided form presents an explosion hazard. Follow NFPA 654 (for chemical dusts) or 484 (for metal dusts) as appropriate for managing dust hazards to minimize secondary explosion potential.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

There are no components with workplace exposure limits.

Engineering Controls

Local Ventilation:None should be needed.General Ventilation:Recommended.

Personal Protective Equipment for Routine Handling

Eyes:	Use proper protection - safety glasses as a minimum.
Skin:	Washing at mealtime and end of shift is adequate.
Suitable Gloves:	Handle in accordance with good industrial hygiene and safety practices.
Inhalation:	No respiratory protection should be needed.
Suitable Respirator:	None should be needed.

according to Regulation (EC) No 1907/2006

TechSil Gum (Part A)

Revision date: 11.06.2019 Personal Protective Equipment for Spills Page 6 of 11

according to Regulation (EC) No 1907/2006

TechSil Gum (Part A)

Page 7 of 11

Eyes:	Use proper protection - safety glasses as a minimum.		
Skin:	Washing at mealtime and end of shift is adequate		
Inhalation/Suitable Respirato:r	No respiratory protection should be needed.		
Precautionary Measures:	Use reasonable care.		
Comments:	When heated to temperatures above 150°C (300°F) in the presence of air, product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate eyes, nose, and throat. Safe handling conditions may be maintained by keeping vapor conditions within the OSHA permissible exposure limit for formaldehyde.		

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added recautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

Revision date: 11.06.2019

Physical Form: Rubber-Crepe Color: Tan Odor: Not available Specific Gravity@ 25°C: 1.1 Viscosity: Not determined. Freezing/Melting Point: Not determined. Boiling Point: Not determined. Vapor Pressure @ 25°C: Not determined. Vapor Density: Not determined. Solubility in Water: Not determined. pH: Not determined. Volatile Content: Not determined. Flash Point: Not applicable. Autoignition Temperature: Not determined. Flammability Limits in Air: Not determined.

Note : The above information is not intended for use in preparing product specifications. Contact Dow Coming before writing specifications.

10. STABILITY AND REACTIVITY

Chemical Stability: Stable.

HazardousHazardous polymerization will not occur.Polymerization:None.

according to Regulation (EC) No 1907/2006

TechSil Gum (Part A)

Revision date: 11.06.2019

Page 8 of 11

Materials to Avoid: Oxidizing material can cause a reaction.

Hazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Carbon oxides and traces of incompletely burned carbon compounds. Silicon dioxide. Formaldehyde.

11. TOXICOLOGICAL INFORMATION

Special Hazard Information on Components

No known applicable information.

12. ECOLOGICAL INFORMATION			
Environmental Fate and I	Distribution		
Air:	This product is a solid consisting of a high molecular weight silicone polymer and other solid materials. Unless milled to produce a dust or particles, it is unlikely to give rise to atmospheric contamination.		
Water:	This product is a solid which is completely insoluble in water. As the specific gravity is >1, it will sink to the bottom of the water course.		
Soil:	This product will enter the terrestrial environment if, as a component of municipal or industrial solid waste the product is landfilled. It is unlikely that further significant transformation of the product will occur.		
Degradation:	High molecular weight polymer which is amenable to recycling. The product is not biodegradable. The product is removed >80% during the sewage treatment process.		
Environmental Effects			
Toxicity to Water Organisms:	This product has low water solubility and should not present a risk to aquatic organisms.		
Toxicity to Soil Organisms	: This product is a solid and does not contain significant concentrations of water soluble constituents that may be leached from the product. It is therefore not likely to present a danger to terrestrial organisms.		
Bioaccumulation:	This product is a solid which is not soluble in water and if ingested will not be absorbed.		
Fate and Effects in Waste	e Water Treatment Plants		

Fate and Effects in Waste Water Treatment Plants

according to Regulation (EC) No 1907/2006

TechSil Gum (Part A)

Revision date: 11.06.2019

Page 9 of 11

This product is a solid rubber type material which is unlikely to have any adverse effect on bacteria.

Ecotoxicitv Classification Criteria			
Hazard Parameters (LC50 or EC50)	High	Medium	Low
Acute Aquatic Toxicity (mg/L)	<=1	>1 and <=100	>100
Acute Terrestrial Toxicitv	<=100	>100 and<= 2000	>2000

This table is adapted from "Environmental Toxicology and Risk Assessment", ASTM STP 1179, p.34, 1993.

This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

13. DISPOSAL CONSIDERATIONS

RCRA Hazard Class (40 CFR 261)

When a decision is made to discard this material, as received, is it classified as a hazardous waste? No

State or local laws may impose additional regulatory requirements regarding disposal. Call (989) 496-6315, if additional information is required.

14. TRANSPORT INFORMATION

DOT Road Shipment Information (49 CFR 172.101)

Not subject to DOT.

Ocean Shipment CIMDG)

Not subject to IMDG code.

Air Shipment (IATA)

Not subject to IATA regulations.

Call Dow Corning Transportation, (989) 496-8577, if additional information is required.

15. REGULATORY INFORMATION

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

EPA SARA Title III Chemical Listings

according to Regulation (EC) No 1907/2006

TechSil Gum (Part A)

Revision date: 11.06.2019

Page 10 of 11

Section 302 Extremely Hazardous Substances (40 CFR 355): None.				
Section 304 CEF None.	RCLA Hazard	ous Substances (40 CFR 302):		
Act Chro F Pressu	Section 311/312 Hazard Class (40 CFR 370): Acute: No Chronic: No Fire: No Pressure: No Reactive: No			
Section 313 Tox None preser		(40 CFR 372): sent in regulated quantities.		
Note: Chemicals ar	e listed under th	ne 313 Toxic Chemicals section only if they meet or exceed a reporting threshold.		
Supplemental S	tate Complia	nce Information		
California				
	prcement Act o	ns the following chemical(s) listed by the State of California under the Safe Drinking Water of 1986 (Proposition 65) as being known to cause cancer, birth defects or other		
None known.				
Massachusetts				
<u>CASNumber</u>	<u>Wt %</u>	Component Name		
7631-86-9	15.0 - 35.0	Silica, amorphous		
New Jersey				
<u>CASNumber</u>	<u>Wt%</u>	ComponentName		
68083-19-2	40.0 - 60.0	Dimethyl siloxane, dimethylvinyl-terminated		
7631-86-9	15.0 - 35.0	Silica, amorphous		
68083-18-1	15.0 - 35.0	Dimethyl, methylvinyl siloxane, dimethylvinyl-terminated		
70131-67-8	70131-67-8 7.0 - 13.0 Dimethyl siloxane, hydroxy-terminated			
ļ				

according to Regulation (EC) No 1907/2006

TechSil Gum (Part A)

Page 111 of 11

None	1.0- 5.0	Dimethylcyclosiloxanes
Pennsylvania		
CAS Number	Wt%	<u>Componen</u> t Name
68083-19-2	40.0 - 60.0	Dimethyl siloxane, dimethylvinyl-terminated
7631-86-9	15.0 - 35.0	Silica, amorphous
68083-18-1	15.0 - 35.0	Dimethyl, methylvinyl siloxane, dimethylvinyl-terminated
70131-67-8	7.0 - 13.0	Dimethyl siloxane, hydroxy-terminated

16. OTHER INFORMATION

Revision date: 11.06.2019

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.